

Model Specification	OPSL90 (dB)		Full-On Gain (dB)		Frequency Range (Hz)	
	Peak	HFA	Peak	HFA	F1	F2
Qin B900-UP DW	137	130	67	55	200	5860
Qin B700-UP DW						
Qin B500-UP DW						
Qin B300-UP DW						
Qin B100-UP DW						
Qin B900-SP DW	134	125	61	50	200	5860
Qin B700-SP DW						
Qin B500-SP DW						
Qin B300-SP DW						
Qin B100-SP DW						
Qin B900-P DW	130	121	57	46	200	5860
Qin B700-P DW						
Qin B500-P DW						
Qin B300-P DW						
Qin B100-P DW						

Model Specification	OPSL90 (dB)		Full-On Gain (dB)		Frequency Range (Hz)	
	Peak	HFA	Peak	HFA	F1	F2
Han B900-SP DW	134	126	64	55	200	6020
Han B700-SP DW						
Han B500-SP DW						
Han B300-SP DW						
Han B100-SP DW						
Han B900-P DW	132	124	60	50	200	6020
Han B700-P DW						
Han B500-P DW						
Han B300-P DW						
Han B100-P DW						

Harmonic Distortion (%)			Equivalent Noise (dB)	Current Drain (mA)
500	800	1600		
3	1	1	29	2.6
3	1	1	29	2.6
3	1	1	29	2.6

Harmonic Distortion (%)			Equivalent Noise (dB)	Current Drain (mA)
500	800	1600		
3	1	1	29	2.6
3	1	1	29	2.6